



SAFETY CHECK AND REGISTRATION FORM

Car Related Items

Safety Decal Serial Number _____

Roll Cage

(Minimum 1" to drivers helmet) _____
(DQ) **Belts** Seat/Shoulder _____
Shoulder, Seat, & Crotch/Anti-Sub belt
required (2 year maximum, SFI 16.1)

Nerf Bars/Bumpers

(Minimum (2) 6/32 bolts, Grade 5 min.) _____

Shoulder Bar

(Min. 8/32 bolt at spud or clamp grade 5 min) _____

(DQ) **Axles/Hubs**

(Axles not past wheels) _____

Belly Pan

(Minimum gauge 0.040 AL, No open holes) _____

Fire Wall

(Minimum gauge 0.048 AL, No open holes) _____

(DQ) **Steering Wheel**

(1" thick, 2" diameter pad, min.) _____

Steering

(Not over center, binds) _____

Ignition System

Brakes

(DQ)(Heel Stop, Metallic outer shield brake line) _____

Fuel System

(Minimum quality wire tie clamp) _____

Fuel Line - Rated for Gasoline or Methanol _____

Fuel Sleeve - Fire Resistant Sleeve _____

(DQ required on all fuel lines) _____

Fuel Filter - Steel or Aluminum Only _____

(DQ) **Exhaust System**

Throttle Cable

(No binding) _____

Tail Cone

(Below top of bumper) _____

Tires/Wheels

(Three lug nuts) _____

(DQ) **Oil Catch Can**

(Located under tail) _____

(DQ) **Weights**

(No weights fastened to side pod sheet metal, lead weights must be bolted and coated or wrapped, fender washers must be included if it's bolted through belly pan)

Side Panels

L _____ R _____

(2" hole for access to flywheel nut, (DQ) maximum 22 inches)

Enclosed Nose Section

DECALS _____

Hoosier, USAC, USAC.25 _____

Drivers Equipment

(DQ) **Helmet**

(Snell SA 2005 (or higher) or SFI 24.1 (or higher)) _____

Face Shield

(No cracks) _____

(SFI 3.2 A/1 minimum) _____

(DQ) **Neck Collar**

(Nomex or Equivalent or Head & Neck Restraint _____

SFI 38.1 Certified)

(DQ) **Arm Restraints**

(Worn close to wrist, not above elbow) _____

(DQ) **Suit 1 or 2 piece**

(SFI 3.2A/1 min. no jeans) _____

(DQ) **Shoes**

(Completely cover feet, flat bottom) _____

(DQ) **Gloves**

(SFI 3.3/5, 1 layer) _____

Effective January 1, 2012, Head and Neck Restraint Systems shall be inspected for recertification every five years after the date of original certification. Product inspection, maintenance, and/or replacement procedure is per individual manufacturer. Inspection must be done by the original manufacturer only, and not their authorized resellers or dealers. When a unit is determined by the manufacturer to be acceptable for continued service and in compliance with the current version of the specification, the original manufacturer shall place on the product a new SFI 38.1 conformance label marked with the inspection date.

General Safety Condition: _____

Safety Director Signature: _____

Registration

Date _____ Car # _____ Color _____

Class: Novice 120 160 Mod AA Animal W/F
Division: Junior Senior Light Heavy Unrestricted

Drivers Name _____ DOB: _____ Age _____

Address _____ City, State, Zip _____

Handlers Name _____ Phone _____

Address _____ City, State, Zip _____

Drivers # _____ .25 Club _____

I agree to assume all responsibility at this event and to abide by all .25 rules/procedures.

Signature of Owner and/or Handler _____

NOTE: (DQ) is reference to item that is a Disqualifiable item from race or timing event.